



LS-50 Motorized Rotary Stage

The inexpensive LS-50 motorized rotary stage accommodates 2" and 50 mm optics. A stepper motor with a geared drive belt generates fast, repeatable motion. A micro-stepping driver and gear reduction enables precise rotary positioning. The stage is available with a 400 step (0.9° per step) motor with or without an encoder for closed loop positioning. A rugged bearing with 4-point contact supports both radial and thrust loads so the stage can be operated horizontally or vertically.

SPECIFICATIONS

- 4"x6"x0.875" footprint plus motor/encoder (thickness); available as shown above or with an encoder
- Optic holder with 2" bore, 1.875" clear aperture
- Precision, slim ball bearing with X-contact races
- Compact 400 step motor, 0.03 degree resolution and >100 rpm guaranteed
- Flexible belt drive with no backlash
- 1-8X microstepping driver, 12-24V power plus step and direction TTL pulses minimum requirement
- Variable speed and direction using logic (TTL) inputs for step and direction
- Rotation rates >100 rpm guaranteed
- Integrated reflective optical home sensor
- Optional encoder with 32-2500 cycles per revolution

Related products: Stepper Motor Controller, Turbulence Phase Plates

Please consult us if your requirements call for different specifications or if you need custom engineering or integration of this product or related products.

LEXITEK Inc.

50 Hunt St Ste 120, Watertown, MA 02472
Tel: (781) 431-9604 Fax: (781) 431-9605
www.lexitek.com